

Komfort 200

Quick Sheet

Solid & Glazed
Movable Wall

Think partitioning.
Think Komfort.

Komfort 200 Quick Sheet



Komfort 200 is a manually operated, top hung, floor supported or floor guided hinged solid and glazed panel moveable wall system. Designed to give economical but long-lasting use in the division of spaces where flexibility is required, with a range configurations available to meet acoustic and operation requirements.

This system allows spaces to be divided quickly and easily but also allow them to open back up when a larger space is required. Where space is at a premium, movable walls allow office and commercial spaces to fulfill different requirements with ease.

Overview

Maximum Screen Height	4000mm*
Maximum Module Width	1200mm
Maximum Doorset Height	11000mm*
Acoustic Performance	Up to 43dB*
Fire Performance	None

* Depending on configuration & specification



Top Hung



Floor Supported



Pivoting Wall



Sliding Door

Optional Extras & Finishes

✓ Polyester Powder Coat Finish	✓ Manifestations	✓ Graphics
✓ Switch Glass	✓ MDF	✓ MFC
✓ Top Hung	✓ Floor Supported	✓ Floor Guided

* Depending on configuration & specification

Performance Summary

Glass & Joint Type	Acoustics		Dimensions		Operation	
	dB Rating	Thickness	Max Width	Max Height	Manual	Automatic
Solid or Glazed Top Hung	42-43 dB	71mm	1050mm	4000mm	✓	✗
Solid or Glazed Floor Supported	42-43 dB	71mm	1050mm	4000mm	✓	✗
Solid or Glazed Operable Wall	42-43 dB	71mm	1200mm	4000mm	✓	✗
Glazed Floor Guided	33 dB	35mm	900mm	3000mm	✓	✗
Glazed Operable Wall	33 dB	35mm	900mm	3000mm	✓	✗
Glazed Sliding Door	33 dB	35mm	900mm	3000mm	✓	✗
Glazed Pivoting Wall	33 dB	35mm	900mm	3000mm	✓	✗

* Depending on configuration & specification. † For heights above 3300mm panels have to be segmented.

Stacking Systems



Type A



Type C



Type E



Centre Fold



Side Stack



Pivoting

For further information please refer to the **Komfort 200** Design Guide or contact our Specification Team.



This product is available on **NBS Source**.

Birmingham Head Office
Tel | +44 (0) 121 332 2560
headoffice@komfort.co.uk



Not currently available for this product.

Specifier Support
Tel | +44 (0) 121 332 2550
specifiersupport@komfort.co.uk



THE INTERNATIONAL EPD® SYSTEM

Not currently available for this product.

Technical Support
Tel | +44 (0) 1403 390 390
technical@komfort.co.uk