

Kross Glaze 600

Quick Sheet



Framed Split
Glazed Partitioning

Think partitioning.
Think Komfort.

Kross Glaze 600 Quick Sheet



Kross Glaze 600 is Komfort's industrial style framed split glazing system with matching rebated acoustic door and can be configured as offset single or double glazed with 90-degree, 135-degree and three-way posts.

Overview

Maximum Screen Height	3000mm
Maximum Module Width	1200mm
Maximum Doorset Height	3000mm
Trackwork Dimensions	54mm
Deflection Head	None
Acoustic Performance	Up to 41dB (R_w)*
Structural Performance	Up to Light Duty
Fire Performance	None


* Depending on configuration & specification



Single Glazed



Double Glazed



Door & Frame

Optional Extras & Finishes

✗ Blinds	✓ Manifestations	✓ Graphics
✓ Kross Glaze Doors	✗ Switch Glass	✗ Curved Glass
✓ Polyester Powder Coat Finish	✗ Satin Anodised Finish	✓ Special Anodised Finish

* Depending on configuration & specification

Performance Summary

Glazing Configuration	Acoustic Performance		Construction Heights	
	Screen	Door	Duty Rating	Max.Height
Single Glazed with 6.8mm Acoustic Laminated	34dB (R_w)	29dB (R_w)	Light	3000mm
Single Glazed with 10.8mm Acoustic Laminated	37dB (R_w)	30dB (R_w)	Light	3000mm
Single Glazed with 12.8mm Acoustic Laminated	38dB (R_w)	33dB (R_w)	Light	3000mm
Double Glazed with 6.4mm & 6.8mm Acoustic Lam.	41dB (R_w)	36dB (R_w)	Light	3000mm

For further information please refer to the **Kross Glaze 600** Design Guide or contact our Specification Team.



NBS Source

This product is available on **NBS Source**.



BIM Objects

Not currently available for this product.



THE INTERNATIONAL EPD® SYSTEM

Not currently available for this product.

Birmingham Head Office

Tel | +44 (0) 121 332 2560
headoffice@komfort.co.uk

Specifier Support

Tel | +44 (0) 121 332 2550
specifiersupport@komfort.co.uk

Technical Support

Tel | +44 (0) 1403 390 390
technical@komfort.co.uk