

## Komfire 75FR Quick Sheet



Komfire 75FR is Komfort's 30/0 to 30/30 fire rated framed solid and glazed partitioning system, constructed with single layered plasterboards and steel internal structure, using 6mm fire glass in single and double glazed configurations with a minimal aluminium trackwork with angular or square stop door frames. The system is fully demountable and relocatable.

Overview	
Maximum Screen Height	3000mm*
Maximum Module Width	1200mm
Maximum Doorset Height	3000mm*
Trackwork Dimensions	96x35mm
Deflection Head	None
Acoustic Performance	Up to 43dB ( <i>R</i> <sub>w</sub> )*
Structural Performance	Up to Medium
Fire Performance	30/0-30/30







\* Depending on configuration & specification

Solid Glazed Door Frame

## **Optional Extras & Finishes**

✓ Blinds\*

✓ Manifestations

✓ Graphics

- ✓ Komfort Doors (Sonik\*, Glass, Timber)
- ✓ Switch Glass 

  \* Curved Glass
- ✓ Polyester Powder Coat Finish
- Satin Anodised Finish
- ✓ Special Anodised Finish

<sup>\*</sup> Depending on configuration & specification

Performance Summary	Acoustics	Acoustics Max. Height Duty Ratings to BS 5234-2:1992				
Solid/Glazed Configuration	dB Rating	Light	Medium	Heavy	Severe	Rating
Solid Single Layered 12.5mm Wallboard with Head Track	43dB ( <i>R</i> <sub>w</sub> )	3000mm	2700mm	-	-	30/0
Solid Single Layered 12.5mm Wallboard with Head F Trim	43dB ( <i>R</i> <sub>w</sub> )	3000mm	2700mm	-	-	30/30
Single Glazed with 6mm Komfort Fire Glass	31dB ( <i>R</i> <sub>w</sub> )	3000mm	2700mm	-	-	30/0
Double Glazed with 6.4mm & 6mm Komfort Fire Glass	39dB ( <i>R</i> <sub>w</sub> )	3000mm	2700mm	-	-	30/0
FD30 Doorsets with 44mm Komfort FD30 Timber Doors	36dB ( <i>R</i> <sub>w</sub> )	-	-	-	-	30/0

For further information please refer to the Komfire 75FR Design Guide or contact our Specification Team.







This product is available on NBS Source.

Not currently available for this product.

THE INTERNATIONAL EPD® SYSTEM

Not currently available for this product.

Birmingham Head Office Tel | +44 (0) 121 332 2560 headoffice@komfort.co.uk Specifier Support
Tel | +44 (0) 121 332 2550
specifiersupport@komfort.co.uk

Technical Support
Tel | +44 (0) 1403 390 390 technical@komfort.co.uk

www.komfort.com KF75FR-QS | Issue 1