

Sonik 52 Quick Sheet



Sonik 52 is Komfort's original minimal 44mm acoustic glazed door, designed to be integrated within all Komfort's partitioning systems and for the ease of installation and future product maintenance. The manufactured doorset can be specified as a single, hospital or double doorset with either lift-off hinges or with an offset pivot and floor spring.

| Overview | | |
|---------------------------|-------------------|--|
| Maximum Doorset Height | 3000mm* | |
| Maximum Door Width | 1100mm* | |
| Maximum Door Weight | 120kg | |
| Profile Dimensions | 52x44mm | |
| Single Doorsets | Yes | |
| Double/Hospital Doorsets | Yes | |
| Max. Acoustic Performance | 37dB (R_{w})* | |
| Max. Fire Performance | None | |
| | | |







* Depending on configuration & specification

Lift Off Hinges

Offset Pivot

Kross Glaze

| \cap | ntiona | Evetron | & Finishes |
|--------|--------|---------|--------------|
| V | puona | EXIIdo | a riilisiles |

| × | Blinds | 1 |
|---|---------------------------|---|
| ✓ | Switch Glass | , |
| ✓ | Integration with Komfire* | , |

Manifestations

- Lift Off Hinge or Offset Pivot
- Powder Coat Finish
- ✓ Graphics
 - Electronic Access Options
- Satin Anodised Finish
- ✓ Kross Glaze Bars
- ✓ Integration with Polar
- ✓ Special Anodised Finish

^{*} Depending on configuration & specification

| Performance Summary | | |
|--|--------------------------------|---------------------|
| Door Type & Glass Configuration | Acoustics | Weight* |
| Double Glazed with 6mm & 6mm Toughened | 37dB (<i>R</i> _w) | 38kg/m ² |

^{*} Weight shown excludes ironmongery













For further information please refer to the Sonik 52 Design Guides or contact our Specification Team.



