

# Sonik 70S

## Quick Sheet



Single Glazed Slimline  
Sliding Acoustic Doors

Think partitioning.  
Think Komfort.

# Sonik 70S Quick Sheet



**Sonik 70S** is Komfort's 28mm offset or pocket sliding acoustic glazed door, designed to be integrated within Komfort's Polar 30 and Polar 100 partitioning systems and for the ease of installation and future product maintenance. Ensuring acoustic insulation is maintained by an automatic drop-down seal and specially designed glazing gaskets. The top hung doors can be specified as a single or double sets with soft-close functionality as standard.

## Overview

|                           |                 |
|---------------------------|-----------------|
| Maximum Doorset Height    | 3000mm*         |
| Maximum Door Width        | 1300mm*         |
| Maximum Door Weight       | 130kg           |
| Profile Dimensions        | 70x28mm         |
| Single Doorsets           | Yes             |
| Double Doorsets           | Yes             |
| Max. Acoustic Performance | 35dB ( $R_w$ )* |
| Max. Fire Performance     | None            |

\* Depending on configuration & specification



Offset Sliding



Pocket Sliding



Kross Glaze

## Optional Extras & Finishes

|                                   |                           |                         |                           |
|-----------------------------------|---------------------------|-------------------------|---------------------------|
| * Blinds                          | ✓ Manifestations          | ✓ Graphics              | ✓ Kross Glaze Bars*       |
| * Switch Glass                    | ✓ Top Hung Sliding System | ✓ Soft Close Function   | ✓ Floor Guide & Drop Seal |
| ✓ Integration with Polar 30 & 100 | ✓ Powder Coat Finish      | * Satin Anodised Finish | ✓ Special Anodised Finish |

\* Depending on configuration & specification

## Performance Summary

| Door Type & Glass Configuration                     | Acoustics      | Weight*             |
|---|----------------|---------------------|
| <b>Single Glazed</b> with 12mm Toughened            | 33dB ( $R_w$ ) | 31kg/m <sup>2</sup> |
| <b>Single Glazed</b> with 10.8mm Acoustic Laminated | 33dB ( $R_w$ ) | 28kg/m <sup>2</sup> |
| <b>Single Glazed</b> with 12.8mm Acoustic Laminated | 35dB ( $R_w$ ) | 32kg/m <sup>2</sup> |

\* Weight shown excludes ironmongery

## Selection of Ironmongery Options



For further information please refer to the **Sonik 70S** Design Guides or contact our Specification Team.

