

## Komfort 200

### At a glance

#### Dimensions:

Height - up to 6000mm  
 Panel width - up to 900 mm  
 Panel thickness - 80mm & 85mm

#### Fire ratings:

N/A

#### Acoustics:

Up to 52dB (Rw)

#### Weight:

Up to 38 kg/m<sup>2</sup>

#### Stacking options:

Centre fold, end fold or eccentric

#### Panels:

Panel construction – aluminium frame

Panel edges – exposed or concealed, SAA or powder coated

Panel type – hinged

Pass door panels – full height only, single or double

Panel finishes – melamine, laminate, veneer, fabric or spray paint

#### Structure:

Suspension method – floor supported with top guide or top hung

Seal type –fixed top and bottom sweep strips



Komfort moveable walls have been designed to give flexibility in the division of spaces.

Komfort 200 is constructed of flat individual or hinged panels designed with the ability to slide and fold to one or both sides within an opening. The Komfort 200 system can be supplied in either top hung or floor supported options.

Think partitioning, think Komfort.

**Birmingham Office/Head Office**  
 Tel: +44 (0)121 332 2560  
 Email: [headoffice@komfort.com](mailto:headoffice@komfort.com)

**Technical Support**  
 Email: [technical@komfort.com](mailto:technical@komfort.com)  
[www.komfort.com](http://www.komfort.com)