Kross Glaze

At a glance

Dimensions:

*Height - up to 3300mm

Fire ratings:

N/A

Acoustics:

*Up to 49dB (Rw)

Structure:

*Up to severe duty

Deflection head:

*+/-15mm, +/-25mm

Door options:

Timber doors

Sonik glazed doors

Single glazed doors

Door frame options:

Aluminium door frame

Glass type options:

Frameless

Toughened – 10mm, 12mm

Acoustic – 10.8mm, 12.8mm

Framed

Toughened – 6mm, 10mm

Weight (including nominal head & base)*:

Frameless single glazed:

Toughened glass

10mm = 27 kg/m2

12mm = 32 kg/m2

Acoustic glass

10.8mm = 28 kg/m2

12.8mm = 33 kg/m2

Frameless double glazed:

Toughened glass

10mm = 54 kg/m2

12mm = 64 kg/m2

Framed:

Glazed - up to 35 kg/m2

✓***Blinds**

✓ **Manifestations**

✓ **Graphics**

✓***SwitchGlass**

Paint/ finishes

✓ **Polyester powder coat**

✓***Satin anodised aluminium**

✓ **Special anodised finish**

* dependent on system configuration / specification

The Kross Glaze system is available in frameless single and double glazed and framed double glazed.

Frameless - The banded glazing is achieved by using a flat aluminium trim which is face applied to the glass using a clear double-sided tape.

Framed - The transoms and mullions are constructed using a range of posts which will vary in dimension depending on the desired system appearance or structural height. Once the main framework is installed various glazing profiles will be used to accommodate either single glazed or double glazed.

Framed double glazed

Frameless single glazed



Frameless double glazed

Think partitioning, think Komfort.

Birmingham Office/Head Office
Tel: +44 (0)121 332 2560
Email: headoffice@komfort.com

Technical Support
Email: technical@komfort.com
www.komfort.com