

Timber Doors & Frames

Doors at a glance

Dimensions:

Maximum bespoke door height
- up to 3000mm

Maximum stock door height -
up to 2700mm

Maximum door width - *up to
1100mm

Fire ratings:

NFR, FD30, FD60

Door acoustics:

Up to 34dB (Rw)

Door thickness:

44mm, 54mm

Door construction:

Doors can be solid or framed
hollow core to suit your
requirements with hardwood
lippings.

Available finishes:

All commercially available
veneers as below:

Ash, American black walnut,
Cherry, Maple, Sapele,
Steamed beech, American
white oak, European oak

Also available: Primed for paint,
full range of laminates

Door vision panels:

Complete range of vision
panels including Approved
Document M compliant options

Frames at a glance

Dimensions:

Frame height/width - *to suit the
timber door sizes available.

Fire ratings:

NFR, FD30, FD60

Available finishes:

See door finishes available
above.

* manufactured to meet your
bespoke design



Komfort's bespoke door range has impressive performance qualities which can be finished with a wide variety of colours and ironmongery options, creating the most beautiful and distinguished environments.

Door types include fire rated doors in a range of veneers, laminates or paint grade for on-site painting, and can be supplied with a choice of vision panel options.

In accordance with Komfort's commitment to responsible and sustainable sourcing, all Komfort's doors can be supplied with full FSC chain of custody prior to manufacture.

Think partitioning, think Komfort.

Birmingham Office/Head Office
Tel: +44 (0)121 332 2560
Email: headoffice@komfort.com

Technical Support
Email: technical@komfort.com
www.komfort.com