

## **Glass Doors** Quick Sheet



Komfort **Glass Doors** perfectly complement a modern office environment. In offices with glass partitions they offer a sleek contemporary aesthetic, glass opens up the workplace for a more creative and cohesive environment. With the offering further complimented by a range of standard ironmongery options, including lever latch sets, back-to-back pull handles and wireless access control if required.

Overview		
Maximum Doorset Height	2700mm*	
Maximum Door Width	1200mm*	
Framed Door Max. Weight	80kg	
Frameless Door Max. Wgt.	100kg	
Sliding Door Max. Weight	120kg	
Acoustic Performance	Up to 31dB ( <i>R</i> <sub>w</sub> )*	
Speech Privacy Potential	Basic	
Fire Performance	None	







\* Depending on configuration & specification

Framed Frameless

Sliding

## **Optional Extras & Finishes**

✓ Manifestations	✓ Graphics	✓ Kross Glaze Bars
------------------	------------	--------------------

Switch Glass ✓ Electronic Access Options

 $<sup>^{\</sup>star}$  Depending on configuration & specification

Performance Summary			
Door Type & Glass Configuration	Acoustic Performance	Weight Excluding Ironmongery	Maximum Weight
12mm Toughened Glass Frameless Sliding Door without Seals	19dB ( $R_{\rm w}$ )	32kg/m <sup>2</sup>	120kg
12mm Toughened Glass Frameless Sliding Door with Seals	$25$ dB ( $R_{\rm W}$ )	32kg/m <sup>2</sup>	120kg
12mm Toughened Glass Frameless Swing Door without Seals	19dB ( <i>R</i> <sub>w</sub> )	32kg/m <sup>2</sup>	100kg
12mm Toughened Glass Frameless Swing Door with Seals	25dB ( $R_{\rm w}$ )	32kg/m <sup>2</sup>	100kg
12mm Toughened Glass Framed Swing Door w/out Drop Seal	$27 dB (R_w)$	32kg/m <sup>2</sup>	80kg
12mm Toughened Glass Framed Swing Door with Drop Seal	31dB ( <i>R</i> <sub>w</sub> )	32kg/m <sup>2</sup>	80kg

For further information please refer to the **Glass Doors** Design Guide or contact our Specification Team.







This product is available on NBS Source.

Not currently available for this product.

THE INTERNATIONAL EPD® SYSTEM

Not currently available for this product.

Birmingham Head Office Tel | +44 (0) 121 332 2560 headoffice@komfort.co.uk Specifier Support
Tel | +44 (0) 121 332 2550
specifiersupport@komfort.co.uk

Technical Support
Tel | +44 (0) 1403 390 390 technical@komfort.co.uk

www.komfort.com SGD-QS | Issue 1