

Polar Double Glazed

At a glance

Dimensions:

Height - up to 3300mm

Acoustics:

Up to 49dB (Rw)

Structure:

Up to severe duty

Deflection head:

+/-15mm, +/-25mm

Door options:

Timber doors

Sonik glazed doors

Single glazed doors

Door frame options:

Aluminium door frame

Timber door frame

Glass type options:

Toughened – 6mm, 10mm, 12mm

Acoustic – 10.8mm, 12.8mm

Weight (including nominal head & base)*:

Toughened glass: 10mm = 54 kg/m²

12mm = 64 kg/m²

✓ Blinds

✓ Manifestations

✓ Graphics

✓ SwitchGlass

✓ Kross Glaze

Paint/ finishes

✓ Polyester powder coat

✗ Satin anodised aluminium

✓ Special anodised finish

* dependent on system configuration / specification




The bubble joint and discreet mullions, or 'ghost posts', and framework of Polar Double Glazed combine contemporary aesthetics, elegance and durability. It is a well-established solution that creates a stunning look in any working environment.

Polar Double Glazed can be integrated with solid partitioning systems through the use of optional head components. Komfort's deflection heads have been designed to achieve the same high-performance standards as the rest of the Polar range whilst incorporating a deflection tolerance of either +/-15mm or +/-25mm.


Standard head detail




Integrated head detail



3-Part +/- 25mm deflection head



2-Part +/- 15mm deflection head



Think partitioning, think Komfort.

Birmingham Office/Head Office

Tel: +44 (0)121 332 2560

Email: headoffice@komfort.com

Technical Support

Email: technical@komfort.com

www.komfort.com