

Defence E Fire Screens

The use of Komfort's Defence E Fire Screens offer integrity performance only. These systems work to prevent the passage of fire, this includes the spread of flame, smoke and toxic gas, but not heat.



	E30	E60
Screens	Up to 4000mm	Up to 4000mm
Acoustic performance	Up to 45dB (Rw)	Up to 45dB (Rw)
Glass-to-glass butt joint	-	-
Frame depth	50mm	50mm
Single Latched doors*	1460x2875mm	1460x2875mm
Double Latched doors*	2980x3370mm	2860x2930mm
Single Unlatched doors*	1370x2540mm	1370x2540mm
Double Unlatched doors*	2390x2540mm	2390x2540mm
Available finish	PPC steel	PPC steel

*Dimensions are clearance between the outer frame. Subject to a maximum leaf area

Think partitioning, think Komfort.

Birmingham Office/Head Office
 Tel: +44 (0)121 332 2560
 Email: headoffice@komfort.com

Technical Support
 Email: technical@komfort.com
www.komfort.com



The Defence EI Fire Screens are constructed using steel tubes and offer fire ratings from 30 minutes to 60 minutes. If you require fire performance higher than 60 minutes, please get in touch with our team see our Defence EI Fire Screens. These systems can also be complemented with both latched and unlatched doors.

Latched and rebated



Non-rebated



For any questions regarding system application, specification or any technical questions, contact our specialist fire screen division.

E: firescreens@komfort.co.uk

Think partitioning, think Komfort.

Birmingham Office/Head Office
Tel: +44 (0)121 332 2560
Email: headoffice@komfort.com

Technical Support
Email: technical@komfort.com
www.komfort.com