

Komfire 100FR

Quick Sheet



30/0-60/60 Fire Rated
Solid & Glazed
Partitioning

Think partitioning.
Think Komfort.


Komfire 100FR is Komfort's 30/0 to 60/60 fire rated framed solid and glazed partitioning system, constructed with single or double layered plasterboards and steel internal structure, using 6mm fire glass in single and double glazed configurations with a minimal aluminium trackwork with angular or square stop door frames. The system is fully demountable and relocatable.

Overview	
Maximum Screen Height	3000mm*
Maximum Module Width	1200mm
Maximum Doorset Height	3000mm*
Trackwork Dimensions	121x35mm
Deflection Head	None
Acoustic Performance	Up to 50dB (R_w)*
Structural Performance	Up to Severe
Fire Performance	30/0-60/60

* Depending on configuration & specification



Solid



Glazed



Door Frame

Optional Extras & Finishes

- ✓ Blinds*
- ✓ Komfort Doors (Sonik*, Glass, Timber)
- ✓ Polyester Powder Coat Finish
- ✓ Manifestations
- ✓ Switch Glass
- ✗ Satin Anodised Finish
- ✓ Graphics
- ✗ Curved Glass
- ✓ Special Anodised Finish

* Depending on configuration & specification

Performance Summary	Acoustics	Max. Height Duty Ratings to BS 5234-2:1992				Fire Rating
		Light	Medium	Heavy	Severe	
Solid/Glazed Configuration	dB Rating					
Solid Single Layered 12.5mm Wallboard with Head Track	43dB (R_w)	3000mm	2700mm	-	-	30/0
Solid Single Layered 12.5mm Wallboard with Head F Trim	43dB (R_w)	3000mm	2700mm	-	-	30/30
Solid Double Layered 12.5mm Wallboard with Head Track	50dB (R_w)	3000mm	3000mm	3000mm	2700mm	60/0
Solid Double Layered 12.5mm Wallboard with Head F Trim	50dB (R_w)	3000mm	3000mm	3000mm	2700mm	60/60
Single Glazed with 6mm Komfort Fire Glass	35dB (R_w)	3000mm	2700mm	-	-	30/0
Double Glazed with 6.4mm & 6mm Komfort Fire Glass	41dB (R_w)	3000mm	2700mm	-	-	30/0
FD30 Doorsets with 44mm Komfort FD30 Timber Doors	36dB (R_w)	-	-	-	-	30/0

For further information please refer to the Komfire 100FR Design Guide or contact our Specification Team.



This product is available on **NBS Source**.



Not currently available for this product.



THE INTERNATIONAL EPD® SYSTEM

Not currently available for this product.

Birmingham Head Office
Tel | +44 (0) 121 332 2560
headoffice@komfort.co.uk

Specifier Support
Tel | +44 (0) 121 332 2550
specifiersupport@komfort.co.uk

Technical Support
Tel | +44 (0) 1403 390 390
technical@komfort.co.uk