

# Komfire 75FR

## Quick Sheet



30/0-30/30 Fire Rated  
Solid & Glazed  
Partitioning

Think partitioning.  
Think Komfort.

**Komfire 75FR** is Komfort's 30/0 to 30/30 fire rated framed solid and glazed partitioning system, constructed with single layered plasterboards and steel internal structure, using 6mm fire glass in single and double glazed configurations with a minimal aluminium trackwork with angular or square stop door frames. The system is fully demountable and relocatable.

Overview	
Maximum Screen Height	3000mm*
Maximum Module Width	1200mm
Maximum Doorset Height	3000mm*
Trackwork Dimensions	96x35mm
Deflection Head	None
Acoustic Performance	Up to 43dB ( $R_w$ )*
Structural Performance	Up to Medium
Fire Performance	30/0-30/30

\* Depending on configuration & specification



Solid



Glazed



Door Frame

### Optional Extras & Finishes

- ✓ Blinds\*
- ✓ Komfort Doors (Sonik\*, Glass, Timber)
- ✓ Polyester Powder Coat Finish
- ✓ Manifestations
- ✓ Switch Glass
- ✗ Satin Anodised Finish
- ✓ Graphics
- ✗ Curved Glass
- ✓ Special Anodised Finish

\* Depending on configuration & specification

Performance Summary	Acoustics	Max. Height Duty Ratings to BS 5234-2:1992				Fire Rating
		Light	Medium	Heavy	Severe	
Solid/Glazed Configuration	dB Rating					
<b>Solid Single Layered</b> 12.5mm Wallboard with Head Track	43dB ( $R_w$ )	3000mm	2700mm	-	-	30/0
<b>Solid Single Layered</b> 12.5mm Wallboard with Head F Trim	43dB ( $R_w$ )	3000mm	2700mm	-	-	30/30
<b>Single Glazed</b> with 6mm Komfort Fire Glass	35dB ( $R_w$ )	3000mm	2700mm	-	-	30/0
<b>Double Glazed</b> with 6.4mm & 6mm Komfort Fire Glass	39dB ( $R_w$ )	3000mm	2700mm	-	-	30/0
<b>FD30 Doorsets</b> with 44mm Komfort FD30 Timber Doors	36dB ( $R_w$ )	-	-	-	-	30/0

For further information please refer to the Komfire 75FR Design Guide or contact our Specification Team.



This product is available on **NBS Source**.



Not currently available for this product.



THE INTERNATIONAL EPD® SYSTEM  
Not currently available for this product.

**Birmingham Head Office**  
Tel | +44 (0) 121 332 2560  
headoffice@komfort.co.uk

**Specifier Support**  
Tel | +44 (0) 121 332 2550  
specifiersupport@komfort.co.uk

**Technical Support**  
Tel | +44 (0) 1403 390 390  
technical@komfort.co.uk